

Safety Data Sheet

Product No. 10033, 14460, 14470, 14464, 14474, 14465, 14477, 14478 PELCO® Pro CA44, C100, C5, C300, C1000, CA-Gel Cyanoacrylate Glue

Issue Date (05-01-15)

Review Date (3-18-16)

Section 1: Product and Company Identification

Product Name: PELCO® Pro CA44 Cyanoacrylate Glue, PELCO® Pro C100 Cyanoacrylate Glue, PELCO® Pro C5 Cyanoacrylate Glue, PELCO® Pro C300 Cyanoacrylate Glue, PELCO® Pro C1000 Cyanoacrylate Glue, PELCO® Pro CA-Gel Cyanoacrylate Glue

Synonym: Super Glue, Instant Adhesive

Company Name

Ted Pella, Inc., P.O. Box 492477, Redding, CA 96049-2477

Domestic Phone (800) 237-3526 (Mon-Thu. 6:00AM to 4:30PM PST; Fri 6:00AM to 4:00PM PST)

International Phone (01) (530) 243-2200 (Mon-Thu. 6:00AM to 4:30PM PST; Fri 6:00AM to 4:00PM PST)

Chemtrec Emergency Number 1-800-424-9300 24 hrs a day.

Section 2: Hazard Identification

2.1 Classification of the substance or mixture according to CLP (1272/2008/EC)

GHS Pictograms



GHS07

GHS Categories

Eye irrit. 2	H319: Causes serious eye irritation
STOT SE 3	H335: May cause respiratory irritation
Skin irrit. 2	H315: Causes skin irritation

2.2 Label elements according to CLP (1272/2008/EC)

Hazard Pictograms



GHS07

Signal Word: Warning

Hazard statements:

H319 Causes serious eye irritation
 H335 May cause respiratory irritation
 H315 Causes skin irritation

EUH202 “Cyanoacrylate. Danger. Bonds skin and eyes in second. Keep out of the reach of children”

Precautionary statements:

P280 Wear protective gloves/protective clothing/eye protection/ face protection
 P304+340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 P332+313 If skin irritation occurs: Get medical advice/attention
 P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P403+233 Store in a well-ventilated place. Keep container tightly closed
 P501 Dispose of contents/container as hazardous or special waste

2.3 Other hazards**Health Effects:**

NFPA Hazard Rating: Health: 2; Fire: 2; Reactivity: 2
 HMIS Hazard Rating: Health: 2; Fire: 2; Reactivity: 2
 (0=least, 1=Slight, 2=Moderate, 3=High, 4=Extreme)

Results of PBT and vPvB assessment: The PBT and vPvB criteria do not apply to ethyl-2-cyanoacrylate

Section 3: Composition / Information on Ingredients

Principle Hazardous Component(s) (chemical and common name(s)) (Cas. No)	%	OSHA PEL mg/m ³	ACGIH TLV mg/m ³	NTP Carcinogen	IARC Carcinogen	OSHA regulated Carcinogen
Ethyl-2-cyanoacrylate (7085-85-0) EC-No. 230-391-5 Index-No. 607-236-00-9 Eye irrit. 2: H319 STOT SE 3: H335 Skin irrit. 2: H315	80 – 99 %	NE	0.2 ppm, 1 mg/m ³ TWA	No	No	No

Section 4: First Aid Measures**If accidental overexposure is suspected**

General: Call a POISON CENTER or doctor/physician if you feel unwell.

Eye(s) Contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If the eye is bonded closed, release eyelashes with warm water by covering with wet pad. Cyanoacrylate will bond to eye protein and will cause periods of weeping which will help to debond the adhesive. Keep eye covered until debonding is complete, usually within 1-3 days. Medical advice should be sought in case solid particles of cyanoacrylate trapped behind the eyelid cause an abrasive damage.

Skin Contact: IF ON SKIN: Wash with plenty of soap and water. Do not pull bonded skin apart. It may be gently peeled apart using a blunt object such as a spoon, preferably after soaking in warm soapy water. Cyanoacrylates give off heat on solidification. In rare cases a large drop will generate enough heat to cause a burn. Burns should be treated normally after the adhesive has been removed from the skin.

If lips are accidentally stuck together apply warm water to the lips and encourage maximum wetting and pressure from saliva inside the mouth. Peel or roll lips apart. Do not try to pull the lips apart with direct opposing action. If skin irritation occurs: Get medical advice/attention.

Inhalation: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If still feeling unwell seek medical attention.

Ingestion: Ensure that breathing passages are not obstructed. The product will polymerise immediately in the mouth making it almost impossible to swallow. Saliva will slowly separate the solidified product from the mouth (several hours).

Section 5: Fire Fighting Measures

Flash Point: 82.5 °C

Flammable Limits: ND

Auto-ignition point: 480 °C

Fire Extinguishing Media: Dry powder, foam, carbon dioxide, fine water spray.

Unsuitable extinguishing agents: water jet.

Special Fire Fighting Procedures: Fire fighters should wear positive pressure self-contained breathing apparatus (SCBA) and suitable protective clothing.

Unusual Fire and Explosion Hazards: Trace amounts of toxic fumes may be released on incineration.

Hazardous combustion products: oxides of carbon, oxides of nitrogen, irritating organic vapors.

DOT Class: none

Section 6: Accidental Release Measures

Steps to be Taken in Case Material is Released or Spilled:

Personal precautions, protective equipment and emergency procedures: Ensure adequate ventilation. Wear protective gloves/protective clothing/eye protection/face protection.

Avoid skin and eye contact. Avoid breathing dust/fume/gas/mist/vapors/spray.

Environmental precautions: Do not let product enter drains.

Methods and material for containment and cleaning up: Do not use clothes for mopping up. Flood with water to complete polymerization and scrape off the floor. Cured material can be disposed of as non-hazardous waste.

Waste Disposal Methods: Dispose of waste according to Federal, State and Local Regulations.

Section 7: Handling and Storage

Precautions to be taken in Handling and Storage: Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Ventilation (low level) is recommended when using large volumes. Use of dispensing equipment is recommended to minimize the risk of skin or eye contact. Wash hands thoroughly after handling. For optimum shelf life store in original containers under refrigerated conditions at 2°C to 8°C. Store locked up.
Storage temperature: 2°C to 8°C
Storage Pressure: ND

Section 8: Exposure Controls / Personal Protection

8.1 Control Parameters

Exposure limit values		
Country	Type	Value
UK	STEL	0.3 ppm; 1.5 mg/m ³ (15 min)
Ireland	OEL/TWA	0.2 ppm
Germany	MAK	No MAK value established
France	VME/VLE	No CME/VLE established

Derived DNEL(s) /DMEL(s)			
Type	Details	Value	Basis
Worker – inhalation route	Systemic effect – Long term exposure	9.25 mg/m ³	irritation (respiratory tract)
Worker – inhalation route	Local effect – Long term exposure	9.25 mg/m ³	irritation (respiratory tract)
General population – inhalation route	Systemic effect – Long term exposure	9.25 mg/m ³	irritation (respiratory tract)
General population – inhalation route	Local effect – Long term exposure	9.25 mg/m ³	irritation (respiratory tract)

Derived PNEC(s)

Tests in aqueous media with ethyl-2-cyanoacrylate with the intent to determine effective concentrations or no effect concentrations cannot be performed due to technical reasons based on the chemical properties of the monomer.

8.2 Exposure Controls

Engineering Controls

Ventilation required: Provide adequate ventilation in area of use. Do NOT use this product in an enclosed or poorly ventilated area. Local exhaust ventilation is normally required when handling or using this product to keep airborne powder below the nationally authorized limits. If ventilation alone cannot control exposure, respiratory protection must be used.

Personal Protection Equipment

Respiratory protection: Ensure adequate ventilation.

Protective gloves: in circumstances where there is a potential for prolonged or repeated skin contact, the use of polyvinyl chloride or nitrile rubber gauntlets or equivalent solvent resistant gloves is recommended. The use of chemical resistant gloves such as Nitrile is recommended. Polyethylene or polypropylene gloves are recommended when using large volumes. Do not use PVC, rubber, nylon or cotton gloves.

Eye protection: Wear protective glasses.

Hygienic measures: Good industrial hygiene practices should be observed. Take off contaminated clothing and wash it before reuse. Wash hand thoroughly after handling.

Exposure Guidelines

See Composition/Information on Ingredients (Section 3)

Section 9 Physical and Chemical Properties

Appearance and Physical State: Transparent, colorless liquid

Odor (threshold): Pungent

Specific Gravity (H₂O=1): 1.043 b/cm³ at 20°C

Vapor Pressure (mm Hg): ≤ 21 Pa

Vapor Density (air=1): ND

Percent Volatile by volume: ND

Evaporation Rate (butyl acetate=1): ND

Boiling Point: 214 °C

Melting point: -31°C

pH: ND

Solubility in Water: ≤ 0.024 mg/l

Molecular Weight: ND

Section 10: Stability and Reactivity

Stability: Stable under normal conditions of storage and use

Conditions to Avoid: Moisture, humidity, basic material

Materials to Avoid (Incompatibility): water, soil, amines, alkalis, and alcohols

Hazardous Decomposition Products: Oxides of carbon, oxides of nitrogen.

Hazardous Polymerization: Will not occur.

Section 11: Toxicological Information

Acute Toxicity

Oral: LD50 (oral, rat) > 5000 mg/kg bw (OECD 401)

Dermal: LD50 (dermal, rabbit) > 2000 mg/kg bw (OECD 402)

Inhalation: In dry atmosphere with < 50% humidity, vapors may irritate the eyes and respiratory system. Prolonged exposure to high concentrations of vapors may lead to chronic effects in sensitive individuals.

Other toxicological effects

Skin corrosion/irritation

Causes skin irritation

Serious eye damage/irritation:

Irritating to eyes. In a dry atmosphere (RH<50%) vapors may cause irritation and lachrymatory effect.

Respiratory or skin sensitization	Due to polymerization at the skin surface allergic reaction is not considered possible. The polymerized material is not able to penetrate into the epidermis.
Germ cell mutagenicity	Because of the reduced exposure to monomer and the reported negative test result in various mutagenicity tests, ethyl-2-cyanoacrylate cannot be classified as mutagen.
Carcinogenicity:	Not carcinogenic
Reproductive toxicity	Not toxic by reproduction
STOT-single exposure	May cause irritation for skin, eyes and respiratory system
STOT-repeated exposure	Ethyl-2-cyanoacrylate is not toxic by repeated absorption
Aspiration hazard	ND
This product does not contain any compounds listed by NTP or IARC or regulated by OSHA as a carcinogen.	

Section 12: Ecological Information

Toxicity	Low ecotoxicity
Persistence and degradability	NA (the test compound would polymerize with contact of water or the moisture of the soil immediately)
Bioaccumulative potential	NA (in presence of moisture ethyl-2-cyanoacrylate polymerizes within seconds)
Motility in soil	NA (the test compound would polymerize with contact of water or the moisture of the soil immediately)
Chemical Fate Information: ND	

Section 13 Disposal Considerations

RCRA 40 CFR 261 Classification: ND

Waste treatment methods

Product disposal:

Cured adhesive: Dispose of as water insoluble non-toxic solid chemical in authorized landfill or incinerate under controlled conditions.

Dispose of in accordance with local and national regulations. Polymerize by adding slowly to water (10:1).

Contribution of this product to waste is very insignificant in comparison to article in which it is used.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorized legal land fill site or incinerated.

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal.

Section 14: Transportation Information

US DOT Information: Proper shipping name: Unrestricted, combustible liquid

IATA: Proper shipping name: Unrestricted, combustible liquid

IMO: Proper shipping name: Unrestricted, combustible liquid

Marine Pollutant: No

Canadian TDG: Unrestricted, combustible liquid

Section 15: Regulatory Information

United States Federal Regulations

SDS complies with OSHA's Hazard Communication Rule 29, CFR 1910.1200.

SARA: None

SARA Title III: None

RCRA: None

TSCA: All components listed

CERCLA: None

State Regulations

California Proposition 65: None

International Regulations

Canada WHMIS: ND

Europe EINECS Numbers: ND

Section 16: Other Information

Label Information: Irritant

European Risk and Safety Phrases: ND

European symbols needed: ND

Canadian WHMIS Symbols: ND

Abbreviations used in this document

NE= Not established

NA= Not applicable

NIF= No Information Found

ND= No Data

Disclaimer

Ted Pella, Inc. makes no warranty of any kind regarding the information furnished herein. Users should independently determine the suitability and completeness of information from all sources. While this data is presented in good faith and believed to be accurate, it should be considered only as a supplement to other information gathered by the user. It is the User's responsibility to assure the proper use and disposal of these materials as well as the safety and health of all personnel who may work with or otherwise come in contact with these materials.