

MATERIAL SAFETY DATA SHEET

Daido Sangyo Co.,Ltd.
NC Bldg., 3-48-2 Minami-Otsuka,
Toshima-ku, Tokyo 170-0005, Japan
Tel +81(3)3984-0384 / Fax +81(3)3984-0453

REVISED 4th December, 2015

Section 1 - Identification of the preparation and company

Trade name: Mount Quick Tube
Manufacturer: Daido Sangyo Co., Ltd.
Emergency tel: +81 3 3984 0384
Product code: Mount Quick Tube
Use of substance / prepareate :
Mounting medium for glass slide

Section 2 - Hazards identification

Hazardous health and Acute Toxicity or Chronic Toxicity:

* This product contains industrial chemicals, avoid skin contact



Signal word : DANGER!

Section 3 - Composition / information on ingredients

Xylene	60,0%	CAS# 1330-20-7
Acrylic resin emulsion adhesive	40.0%	CAS# 64742-95-6

Section 4 - First-aid measures

* Skin contact:

In case of being contacted the skin, wash thoroughly with soap and water, liquid extremely.

* Eye contact:

Irritating to eye, flush with plenty of water - call a physician.

* If swallowed and emergency procedure
Vomits and seek medical help.

* Antidote

Section 5 – Fire-fighting measures

Suitable extinguishing media:

- * Ordinary chemical extinguisher, PVA 10% aqueous solution or 10% gum arabic aqueous solution

Extinguish Method

- * Fire extinguisher

Section 6 - Accidental release measures

Protect hand with glove and wipe it off with a waste.

Collect in the container which can be sealed.

Section 7 - Handling and storage

Handling:

- * Keep away from heat and open flame and small children directions.
- * In case of skin contact flush with plenty of water.

Storage:

Keep from heat and open flame, strong oxidants and small children.

Storage temperature:

25°C

Section 8 - Exposure controls / personal protection

Use in a well-ventilated place and keep from heat and open flame.

Section 9 - Physical and chemical properties

physical state:	liquid
appearance:	colorless
solubility in water(at20°C):	5%
boiling point:	130°C
viscosity(at 20°C):	33 cps
specific gravity:	0.89sp
vapour pressure(at 20°C):	20 mmHg
vapour Density(air-1):	0.95

Section 10 - Stability and reactivity

Conditions / substances to avoid:

Stable under normal conditions.

Use in well ventilated area and keep from heat and open flame.

Section 11 - Toxicological information

Not available

Section 12 - Ecological information

Not available

Section 13 - Disposal considerations

Observe all state and local environmental regulations regarding waste disposal.

Section 14 - Transport information

UN number, hazard class, packing group

* Xylene	1307, 3, II
* Acrylic resin emulsion adhesive	none, 3, II

Section 15 - Regulatory information

Depends on the laws and ordinances of each country

Section 16 - Other information

not available

end of safety data sheet