



PARAFFIN DISPENSER

Microprocessor controlled with heated, non-drip spigot. A clear lid permits easy viewing of paraffin without contamination. The durable stainless steel interior is easy to clean. It features a built-in temperature controller that allows setting the temperature from room temperature to 72°C (162°F).

- 28151 Paraffin Dispenser, 2.5 Gallon Capacity, 110VAC, 50/60Hz, 10Aeach
- 28151-230 Paraffin Dispenser, 2.5 Gallon Capacity, 220VAC, 50/60Hz, 10Aeach



BLOCK WAX TRIMMER

The Block Wax Trimmer is an efficient appliance for removing excess paraffin from embedding tissue cassettes and can be used with all sizes of biopsy and mega cassettes. The grooved, heated surface channels melt wax into a removable collection tray that stays in place at the base of the unit by magnetic contact. Disposable plastic liners are included to insert inside the collection tray for easy disposal of the runoff wax. There are two heat settings on the side of the cabinet; low is approximately 27°C (81°F) and high is approximately 32°C (90°F).

- 23154 Block Wax Trimmer, 115V, 60Hz, 1.4A.....each
- 23154-230 Block Wax Trimmer, 230V, 50/60Hz, 1.4A.....each
- 23154-10 Disposable Replacement Liners for Collection Tray..... pkg/50



TISSUE FLOATATION WATER BATH

The glass Tissue Floatation Water Bath has been developed using microprocessor controls and a modular design that has improved reliability and precision. The unit is low profile with a removable rectangular glass basin for easy cleaning. The glass basin is illuminated by LED light from the side allowing clear observation without glare against the black background. There is an ON/OFF switch on the control panel for the LED light. Temperature settings are controlled by push buttons for accurate and precise control and the easy-to-read LED displays show both set temperature and actual temperature. The corrosion resistant, stainless steel temperature probe flips down into place. The probe has a thermostat sensor inside that turns off when it is lifted up and re-starts when placed back into the basin.

- 28156 Programmable Tissue Floating Bath, 115VAC, 5A.....each
- 28156-230 Programmable Tissue Floating Bath, 230VAC, 2.5A.....each



BIOMEGA HOT PLATE, MAGNETIC STIRRER OR HOT PLATE-STIRRER

Biomega hot plates, magnetic stirrers and hot plate-stirrers feature an exceptionally durable, chemical resistant white ceramic work surface. Their space-efficient design makes them ideal for use on crowded benchtops and inside of bio-hoods.

Advanced microprocessor controls with convenient turn knobs allow quick, precise adjustment and maintenance of speed and temperature. Safety indicator LED's on front panel indicate when the heating or stirring functions are activated. Body made of sturdy, powder coated, cast aluminum.

- 3233 Magnetic Stirrer, P40-S, 115V.....each
- 3234 Hot Plate, P40-H, 115V.....each
- 3235 Hot Plate & Magnetic Stirrer, P40-HS, 115V.....each

MINI SECTION/SLIDE DRYER



The Mini Section/Slide Dryer has a small footprint designed to be used at the microtome. Air at a digitally controlled temperature is blown through the base of the instrument for rapid and efficient section drying. Drying times can be reduced by approximately 75% compared to conventional ovens.

A large chamber has space for up to 6 slide racks (30 slide capacities). Innovative resistance hinges on the lid allows users to easily position it at any angle. With the optional 4 Slide Rack Holder in place, the capacity is reduced to 4 slide racks of 30 slide capacity. The optional LEAN Timer system and 4 Rack Identifier ensures that each slide rack has an exact optimal drying time with an audible and visual indication when a slide rack has completed drying. The LEAN Timer can monitor up to four slide racks.

Dimensions: Width 265mm, Depth 385mm, Height 228mm

| | | |
|---------|---|------|
| 28148 | Mini Section/Slide Dryer, 115V to 250V, 50- 60Hz..... | each |
| 28148-1 | Mini Section/Slide Dryer 4 Rack LEAN Timer Unit | each |
| 28148-2 | 4 Slide Rack Holder/Identifier | each |

STEP UP™ SLIDE WARMER FOR 40 SLIDES



The Step Up™ Slide Warmer has a unique design to save space and assist in efficient handling of a high volume of slides. The Step Up™ Slide Warmer holds twice the number of slides as a flat unit of similar dimensions. The overall dimensions are 14" x 14" x 4" (35.5 x 35.5 x 10.2cm) with digital temperature control and LED readout. Essential for use in histology, pathology or research performing routine stains or immunohistochemistry, this unit has thermostatic temperature control from room temperature to 70°C (158°F) and allows easy access for slide retrieval

| | | |
|-----------|--|------|
| 12856 | Step Up™ Slide Warmer, 115V, 60Hz | each |
| 12856-230 | Step Up™ Slide Warmer, 230V, 50/60Hz | each |



LARGE AND SMALL SLIDE WARMERS

Available with a large capacity 56-slide plate or a compact, small 24-slide plate, these high quality, quick-drying slide warmers are ideal for either the high volume clinical laboratory or the smaller histology or research lab.

The large slide warmer provides a higher volume laboratory an excellent tool for drying paraffin sections in minutes in order to perform routine staining or immunohistochemistry, while the small warmer is perfect for use in histology, pathology and life science research for drying paraffin tissue sections.

Each warmer is equipped with digital temperature control and an LED readout. Thermostatic temperature control from room temperature to 70°C (158°F). Anodized black working surfaces provide excellent contrast.

Large Surface Plate - 56 Slides: 63.5 x 20.3 x 7.6cm (25" x 8" x 3")
 Small Surface Plate - 24 Slides: 25.4 x 17.8 x 7.6cm (10" x 7" x 3")

| | | |
|-------------|--|------|
| 12858-D | Large Slide Warmer, 115V, 60Hz, 1.8A | each |
| 12858-220-D | Large Slide Warmer, 230V, 50/60Hz, 0.9A | each |
| 12857-D | Small Slide Warmer, 115V, 60Hz, 1.2A | each |
| 12857-220-D | Small Slide Warmer, 230V, 50/60Hz, 0.6A | each |
| 12859-D | Small Slide Warmer with Hinged Cover, 115V, 60Hz, 1.2A..... | each |
| 12859-220-D | Small Slide Warmer with Hinged Cover, 230V, 50/60Hz, 0.6A..... | each |
| 12860-D | Large Slide Warmer with Hinged Cover, 115V, 60Hz, 1.8A..... | each |
| 12860-220-D | Large Slide Warmer with Hinged Cover, 230V, 50/60Hz, 0.9A..... | each |